



High Speed Internet Router

4G SIM WiFi-6 Router

Wi-Fi 6: Unleash the Speed, Connect Smarter,
with Cofe Sim Based Routers and
Experience the Future of Wi-Fi.

CF-4G-807 WDIIS WiFi-6



4G LTE



2.4 GHZ



IMEI Based



Nano Sim Support



No Congestion



WiFi+Lan/Wan



Faster Internet



Zero Latency



AI Based Router



All GSM Support

Specification

General	
Net Weight	0.340kg
Packing List	1N Wi-Fi 6 Router, 1N Power Cable, 1N CAT5e × LDPA Antenna/ 10mtr Coaxial Cable × Mount Kit Network Cable × 1N Quick Start Guide
Packing Method	Single pack
Working Temperature	-20° C to 70° C
Storage Temperature	-40° C to 85° C
Working Humidity	10% to 90% RH non-condensing
Installation Mode	Table-Top - Wall Mount
Wireless Parameter	
Wi-Fi	2.4GHz: IEEE 802.11 b/g/n/ac/ax WiFi 6 286.8Mbps@TX and 229.4Mbps@RX with 20/40MHz bandwidth
Wireless Standard	IEEE 802.11b/g/n/ac/ax @2.4GHz
Working Frequency Band	2.4 GHz
Wireless Range	100 Mtr Radial
Max. Connections	32
Transmitting Power	LTE: +23_+ 2dBm
Bandwidth	<20/40 MHz (2.4GHz) bandwidth
Wireless Features	Single Band Supported,MU-MIMO Supported
Antenna	2 External antennas with LPDA Signal Booter
Hardware Parameter	
LED Indicator	Red Led;- Power Blue Led;- Internet
LED Discreption	Red blink ;- wireless user connected Blue blink ;- Network searching
Button	Reset Button
SIM Slot	NANO SIM

RAM	64MB
ROM	64MB
LAN Port	CAT5 Ethernet
Network Band	FDD : B1/B3/B5/B8 ; TDD : B40/B41 Oversea Operator Band Customised
Power Supply Method	Power Supply Adapter
Power Rating	DC 5V2A / 12V1A
Power Input	DC Input
Max. Power Consumption	12≤W
Software Function	
Operating Mode	Wireless Mode
Router Default IP	192.168.150.1
Login Interface ID	User Name: - admin Password: - admin
Default SSID/WIFI Name	COFEXXXX (Can be Modified)
Default SSID Password	12345678 (Can be Modified)
WAN Mode	Static IP PPPOE
DHCP	DHCP Client List DHCP Server
Parental Control	Speed Limit, Internet Access Period, Filter URL, Custom Profiles
IP Version	IPv4, IPv6, Support fast and secure WPS connection Support hiding wireless network name
Security Mechanism	Support Firewalls, Login Authentication
Firewall	Port Mapping; Port forwarding; Port filtering; URL filtering; UPNP; DMZ
VPN	PPTP Client, L2TP Client
Security Mode	WPA2-PSK,WPA/WPA2-PSK Supported
Management Method	Web UI

LPDA

Device Name	LPDA External Antenna
Network DBI	-12dbm
Network Signal Range	Upto 5kM