



AI IP CCTV Camera

This high-definition dome camera is engineered for clear surveillance in low or no-light environments. Ideal for warehouses, tunnels, underground parking lots, streets, bars, and other dimly lit areas, it delivers sharp, reliable footage day and night, ensuring uninterrupted security in any condition.



CF-IP-PDL06



Automatic ICR



IR Night Vision



Human Detection



Mobile Monitoring



Two-Way Talk



Multi-Platform Support



Automatic Electronic Shutter



Alarm Push Notification



Support Onvif



Support PoE

Specification

Camera

Megapixel	3MP / 4MP / 5MP / 6MP / 8MP
Image Sensor	illumination CMOS sensor
Min. Illumination	Color: 0.01Lux @ (F1.2AGC ON): 0 Lux with IR B/W: 0.001Lux @ (F1.2AGC ON): 0 Lux with IR
Shutter Speed	1/50(1/60)s to 1/10,000s
Lens	3.6mm, 4mm, 6mm
Day & Night	IR Cut Filter with Auto Switch

Network

Storage	Network storage
PoE	Support
Protocol	TCP/IP, HTTP, DHCP, DNS, DDNS, PPPoE, SMTP, NTP, HTTPS, SIP, 802.1x, IPV6 Option
Security Features	Video Loss, Video Blocking, Power Protection, Password Protection

Compression

Video Compression	H.265 AI (Compatible H.265/H.264) High Profile, JPEG Snapshot
Bite Rate	0.1 Mbps ~ 8 Mbps
Audio Compression	G.711a

Interface

Ethernet	1*10/100 Mbps Ethernet port, RJ45 Port
Audio Input	Mic
Audio Output	Speaker, External Using Audio Wire

Image	
Max.Image Resolution	2048*1536, 2560*1440, 2560*1920, 3072*2048, 3840*2160
Frame Rate	Up-To 25fps,
General	
Operating Temperature	-10°C ~ 65°C
Operating Humidity	10%-90% RH
Power Input	DC 12V ± 10%/POE
IR Range	IR Range Up To 25 Mtrs
Housing	ABS High Quality Plastic
Consumption	Up-To 4 Watt
Zoom	Digital Zoom Applicable
Light	Dual Array Flood Light
Mounting	Wall Mount, Ceiling Mount
Features	Face Detection, Human Detection, Motion detection
Supported Device	Android, IOS

► Use Cofeonline App to View Your Device

